

Specifications

Engine / Blade Housing

Engine	Honda GX160
HP	5.5
kW	4.1
Grinding Width	8"
Production Rate	350 - 500 ft ² /hr
Depth Per Pass	1/8"
Operating Weight	135 lbs
Dimensions	18" x 18" x 42"

Tungsten Carbide Drum


Material	Tungsten Carbide
Blade/Drum Lifetime	6,000 - 10,000 ft ²
Carbide Cutter Quantity	64
Hardened Washer Quantity	128
Rough Surface Texture	7 3/4" path
Cutter Inside Diameter	0.646"
Cutter Outside Diameter	1.572"
Drum Weight	25"
Drum Dimensions	8" x 4" x 4"



Simple Depth Crank for Lowering Blades



OSHA Approved Vacuum for Dust Reduction



64 Tungsten Carbide Cutters
128 Hardened Washers

FEATURES

- Scarifies 350 - 500 ft²/hour at 1/8" Depth Per Pass
- Remove traffic lines at 800 - 1,000 linear feet per hour
- Engine raised over drum to maximize surface contact
- Front-mounted lifting handle for simple loading/unloading
- OSHA Approved Vacuum port equipped to fit most bags or Wet/Dry Vacuums
- Reduced vibration for optimal user comfort
- 3 Year Engine Warranty & 1 Year Product Warranty



Honda GX160 Engine
5.5HP / 163cc



Tungsten Carbide
Drum Blades



OSHA Approved Dust
Prevention System



3 Year Engine Warranty
1 Year Product Warranty



FIX TRIP HAZARDS SAVE THOUSANDS

Tomahawk Scarifiers are perfect for sidewalk trip hazard repair, traffic line/marking removal, and more. Grind and level 350-500 ft²/hour at a depth 1/8" per pass!



Item #: TSCAR-8H

**GAS-POWERED
CONCRETE SCARIFIER**

www.tomahawk-power.com

